




The products are 15MBd high-speed opto-couplers in the SOP5 package. The device consists of a 850 nm AlGaAs LED, optically coupled to a very high speed integrated photo-detector logic gate with a strobable output. The output end of the product is a CMOS output, and the product has a strong common mode rejection capability. The coupled parameters are guaranteed over the temperature range of -40°C to +110°C. The products are widely used in communication interface, digital isolation for A/D, D/A conversion, high-voltage power systems, renewable energy inverters, medical imaging and patient monitoring.



- High isolation 3750 VRMS
- High speed – 15MBd typical
- Operating temperature range -40°C to 110°C
- REACH & RoHS compliance
- HBM: H3A; MM: M4; CDM: C3
- CQC approved
- VDE approved
- UL approved

LED	Output
ON	L
OFF	H

(Temperature=25°C)

Input	Forward Current	$I_F$	50	mA
	Peak Forward Current	$I_{FP}$	1	A
	Reverse Voltage	$V_R$	6	V



	Input Power Dissipation	$P_D$	100	mW
Output	Supply Voltage	$V_{CC}$	7	V
	Output Voltage	$V_O$	$V_{CC}+0.5$	V
	Output Current	$I_O$	10	mA
	Output Power Dissipation	$P_O$	22	mW
Total Power Dissipation		$P_{tot}$	130	mW
Isolation Voltage		$V_{iso}$	3750	V <sub>rms</sub>
Operating Temperature		$T_{opr}$	-40~110	
Junction Temperature		$T_j$	125	
Storage Temperature		$T_{stg}$	-55~125	
Soldering Temperature		$T_{sol}$	260	

: 100 $\mu$ s pulse, 100Hz frequency

: AC for 1minute, R.H.=40~60%

(Temperature=25°C)

Input	Forward Voltage	$V_F$	$I_F=10mA$	-	1.35	1.6	V
	Input Reverse Breakdown Voltage	$BV_R$	$I_R=10\mu A$	5	-	-	V
	Reverse Current	$I_R$	$V_R=6V$	-	-	1	$\mu A$
	Input Capacitance	$C_{in}$	$V=0, f=1MHz$	-	30	100	pF
Output	High Level Supply Current	$I_{CCH}$	$V_{CC}=5V, I_F=0mA$	-	-	6.5	mA
	Low Level Supply Current	$I_{CCL}$	$V_{CC}=5V, I_F=10mA$	-	-	6.5	mA
	Logic High Output Voltage	$V_{OH}$	$I_F=0mA, I_O=-20\mu A$	$V_{DD-0.1}$	$V_{DD}$	-	V
	Logic Low Output Voltage	$V_{OL}$	$I_F=7mA, I_O=20\mu A, V_{CC}=5V$	-	0.02	0.1	V
	Isolation Resistance	$R_{iso}$	DC500V 40~60%R.H.	$10^{12}$	-	-	
	Floating Capacitance	$C_{IO}$	$f=1MHz$	-	0.6	-	pF
Switching Characteristics	Trigger LED Current	$I_{FT}$	$V_{CC}=5V$	-	-	5	mA




	Propagation Delay Time to Logic Low	TPHL	$I_F=7mA, C_L=15pF$	-	70	100	ns
	Propagation Delay Time to Logic High	TPLH	$I_F=7mA, C_L=15pF$	-	55	100	ns
	Common Mode Transient Immunity at Logic High	CM <sub>H</sub>	$I_F=0mA,$ $V_{CM}=1000V_{pp},$ $C_L=15pF,$ $V_{CC}=5V$	20	-	-	kV/ $\mu$ s
	Common Mode Transient Immunity at Logic Low	CM <sub>L</sub>	$I_F=7mA,$ $V_{CM}=1000V_{pp},$ $C_L=15pF,$ $V_{DD}=5V$	20	-	-	kV/ $\mu$ s

Operating Temperature	T <sub>a</sub>	-40	-	105		
Supply Voltage	V <sub>CC</sub>	2.7	-	5.5	V	
Low Level Input Current	I <sub>FL</sub>	0	-	250	$\mu$ A	
High Level Input Current	I <sub>FH</sub>	8	-	16	mA	
Forward Voltage	V <sub>F(OFF)</sub>	-	-	0.8	V	







Forward Current vs. Forward Voltage




Max. Allowable LED Forward Current vs. Ambient Temperature




Logic High Output Supply Current vs. Ambient Temperature




Logic Low Output Supply Current vs. Ambient Temperature



Propagation Delay vs. Ambient Temperature




Input Threshold Current vs. Ambient Temperature











Propagation Delay vs. Ambient Temperature





Propagation Delay vs. Ambient Temperature






Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.80	0.173		0.189
B	3.60		4.20	0.142		0.165
C	0.00		0.20	0.000		0.008
D	1.90		2.30	0.075		0.091
E	5.00		5.60	0.197		0.220
F	0.34		0.94	0.013		0.037
G	6.70		7.30	0.264		0.287
H	0.10		0.30	0.004		0.012
I	2.00		2.40	0.079		0.094
J	0.25		0.55	0.010		0.022
K	1.02		1.52	0.040		0.060





Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
D0			1.60			0.063
P0	3.90		4.10	0.154		0.161
P1	7.90			0.		.
P2						
E						
F						
T						
W						

7.9



Temperature Min. (T <sub>smin</sub> )	100	150
Temperature Max. (T <sub>smax</sub> )	150	200
Time (t <sub>s</sub> ) from (T <sub>smin</sub> to T <sub>smax</sub> )	60-120 seconds	60-120 seconds
Ramp-up Rate (t <sub>L</sub> to t <sub>P</sub> )	3 /second max.	3 /second max.
Liquidus Temperature (T <sub>L</sub> )	183	217
Time (t <sub>L</sub> ) Maintained Above (T <sub>L</sub> )	60-150 seconds	60-150 seconds



---

Note:

1. Reflow soldering is recommended at the temperatures and times shown, no more than three times.
2. Avoid direct contact between the epoxy body and any tools or surfaces exceeding its maximum storage temperature.
3. Application of pressure on the epoxy body is prohibited at elevated temperatures. In specific scenarios, any applied force must not exceed 2.5N.
4. Ensure the component has cooled to ambient temperature before proceeding with any subsequent manufacturing steps.
5. The component has a shelf life of one year when stored under standard conditions.
6. Recommend storage Temp.: 0~40°C;  
Recommend storage humidity: <60%;  
MSL level: MSL 1

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2026 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.