




The products are 4-pin thyristor opto-couplers. The device combines an AlGaAs infrared emitting diode as the emitter which is optically coupled to a monolithic silicon random-phase photo triac in a plastic SOP4 package. With the robust coplanar double mold structure, the device provides the most stable isolation feature. The products are widely used in solenoid/valve controls, lighting controls, motor controls, temperature controls, static AC power switches, solid state relays, interfacing microprocessors up to 265 V_{AC} peripherals.



- High isolation 3750 VRMS
- DC input with random-phase photo triac output
- Operating temperature range -55 to 110
- REACH & RoHS compliance
- HBM: H3A; MM: M4; CDM: C3
- CQC approved
- VDE approved
- UL approved

(Temperature=25°C)

Parameter		Symbol		Value	Unit
Input	Forward Current	I _F		50	mA
	Peak Forward Current	I _{FP}		1	A
	Reverse Voltage	V _R		6	V
	Power Dissipation	P _D		75	mW
Output	Off-state Output Terminal Voltage	V _{OFF}	JOCSR21X	600	V
			JOCSR31X	800	
	Peak On-state Current (100µs pulse, 120 pps)	I _{TP}		2	A
	On-state RMS Current	I _{T(RMS)}		100	mA
	Peak Repetitive Surge Current (P _W =10 ms)	I _{TSM}		1.2	A
Output Power Dissipation		P _O		250	mW
Total Power Dissipation		P _{tot}		325	mW

Isolation Voltage	V_{iso}	3750	Vrms
Operating Temperature	T_{opr}	-55~110	
Junction Temperature	T_j	125	
Storage Temperature	T_{stg}	-55~125	
Soldering Temperature	T_{sol}	260	
Peak pulse voltage ($T_j=25$; non-repetitive,off-state)	V_{pp}	1	kV

: 100 μ s pulse, 100Hz frequency

: AC for 1minute, R.H.=40~60%

(Temperature=25°C)

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	
Input	Forward Voltage	V_F	$I_F=10mA$	-	1.2	1.5	V	
	Reverse Current	I_R	$V_R=6V$	-	-	1	μA	
	Input Capacitance	C_{in}	$V=0, f=1kHz$	-	14	-	pF	
Output	Peak Off-state Current, Either Direction	I_{OFF}	$V_{OFF}=Rated V_{OFF}$ $I_F=0$	-	-	100	nA	
	Peak On-state Voltage, Either Direction	V_{TM}	$I_{TM}=100mA$	-	2	2.5	V	
	Critical Rate of Rise of Off-state voltage	dV/dt	$V_{PEAK}= Rated V_{PEAK}$ $I_F=0$	2000	-	-	V/ μ s	
Transfer Characteristics	LED Trigger Current	JOCSR21A JOCSR31A	I_{FT}	Terminal Voltage=3V $I_{TM}=100mA$	-	-	10	mA
		JOCSR21B JOCSR31B			-	-	5	
		JOCSR21C JOCSR31C			-	-	3	
	Holding Current	I_H	$I_{TM}=2mA,$ $I_F=Rated I_{FT}$	-	500	-	μA	
	Isolation Resistance	R_{ISO}	DC500V 40~60%R.H.	10^{12}	10^{14}	-		
	Floating Capacitance	C_{IO}	$V=0,$ $f=1MHz$	-	5	-	pF	
	Response Time	t_{on}	$V_D=6V,$ $R_L=100$, $I_F=20mA$	-	15	50	μs	

: Test voltage must be applied within dV/dt ratings

: Refer to Fig.14 & Fig.15

JOCSR21X,JOCSR31X

FIG.7: Normalized On-state Terminal Voltage vs. Ambient Temperature




FIG.8: On-state Terminal Voltage vs. On-state Terminal Current




FIG.9: Normalized Holding Current vs. Ambient Temperature




FIG.10: Turn On Time vs. Forward Current




FIG.11: Normalized Turn On Time vs. Ambient Temperature




FIG.12: Test Circuits of Turn On Time




FIG.13: Waveforms of Turn On Time




Fig.14: Test Circuits of dV/dt




Fig.15: Waveforms of dV/dt








FIG.16: Test circuit for inductive and resistive loads to IEC-61000-4-5 standards





Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.80	0.173		0.189
B	3.60		4.20	0.142		0.165
C	0.00		0.20	0.000		0.008
D	1.90		2.30	0.075		0.091
E	5.00		5.60	0.197		0.220
F	0.34		0.94	0.013		0.037
G	6.70		7.30	0.264		0.287
H	0.10		0.30	0.004		0.012
I	2.00		2.40	0.079		0.094
J	0.25		0.55	0.010		0.022
K	2.29		2.79	0.090		0.110





Profile Feature	Sn-Pb Assembly Profile	Pb-Free Assembly Profile
Temperature Min. (T _{smin})	100	150
Temperature Max. (T _{smax})	150	200
Time (t _s) from (T _{smin} to T _{smax})	60-120 seconds	60-120 seconds
Ramp-up Rate (t _L to t _P)	3 °/second max.	3 °/second max.
Liquidus Temperature (T _L)	183	217
Time (t _L) Maintained Above (T _L)	60-150 seconds	60-150 seconds
Peak Body Package Temperature	235 +0 /-5	260 +0 /-5
Time (t _P) within 5 ° of 260	20 seconds	30 seconds
Ramp-down Rate (T _P to T _L)	6 °/second max.	6 °/second max.
Time 25 ° to Peak Temperature	6 minutes max.	8 minutes max.

Note:

1. Reflow soldering is recommended at the temperatures and times shown, no more than three times.
2. Avoid direct contact between the epoxy body and any tools or surfaces exceeding its maximum storage temperature.
3. Application of pressure on the epoxy body is prohibited at elevated temperatures. In specific scenarios, any applied force must not exceed 2.5N.
4. Ensure the component has cooled to ambient temperature before proceeding with any subsequent manufacturing steps.
5. The component has a shelf life of one year when stored under standard conditions.
6. Recommend storage Temp.: 0~40°C;
Recommend storage humidity: <60%;
MSL level: MSL 1

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for patent infringement.